

Product datasheet

Specifications



APC Performance SurgeArrest 6 outlets with 5V, 2.4A 2 port USB charger, 230V UK

PM6U-UK

Overview

Lead time Usually in Stock

Main

Main Input Voltage 230 V
Input Connection Type BS1363A British
Cable length 2.00 m
Number of cables 1
Provided equipment User manual

Physical

Colour White
Height 6.2 cm
Width 27.2 cm
Depth 11 cm
Net weight 0.81 kg
Mounting preference No preference
Mounting mode Not rack-mountable

Input

Network frequency 50 Hz +/- 5 Hz
Maximum input current 13 A
Switching current capacity 13 A

Output

Number of power socket outlets 6
Outlet standard BS 1363 United Kingdom

Conformance

Product certifications CE
Equipment protection policy Lifetime : \$50000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...4572.00 m

Surge Protection and Filtering

Common mode rejection	40 dB
Peak current	48 kAcommon mode 24 kAnormal mode
Surge energy rate	1836 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31 cm
Package 1 Width	6.5 cm
Package 1 Length	16.5 cm
Package 1 Weight	0.93 kg
SCC14	10731304313653

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	Limited Lifetime (European Union countries only)
----------	--

Recommended replacement(s)